

Recommended P.C.B Layout

MATERIAL



Insulator : NYLON 46
 Contact Pin : Phosphor Bronze

SPECIFICATION

Current Rate : 1 AMP
 Insulation Resistance : 5000MΩMin.
 Contact Resistance : 20mΩMax.
 Dielectric Voltage : AC 500V for one minute
 Operation Temperature : -40°C to + 105°C

621-5 2- 17 G B S0
 1 2 3 4 5

1. 1: Single row
2. 2: Dual rows
3. G: Gold flash
T: Tin plated
4. B: Black Insulator
W: White Insulator
5. Pinrex internal code.

				TOLERANCE .0 = ±.30 .00 = ±.20 .000 = ±.XXX .0000 = ±. ANG. = ±3°		 UNITS : mm		OLD PART NO. CRPS2M43-217GB		TITLE FEMALE HEADER 2.0*2.0mm S/T TYPE, DUAL ROWS, CAP+T/R HEIGHT 4.3mm, P.S.A. TYPE		 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.	
A	RELEASE	2003/07/03		SCALE NONE		SIZE A4		DRAWER Amy		CHECK		NEW PART NO. 621-52-17GBS0	
REV.	DESCRIPTION	DATE		SCALE NONE		SIZE A4		SHEET 1 OF 1		REV. A		DRAW NO. 621-52-17GBS0	